

GPI DAM PUMP

FULL PASTURE IRRIGATION WHEN YOU DON'T HAVE MAINS POWER

Integrated shut off system turns off the dam pump engine when the GreenPro irrigator has finished its run. Added Towing Capability with the 50mm ball hitch. Lightweight construction allows you to transport the pump between creeks and dams easily. Water pressure where you need on your property when

mains power is not available near your dam or creek water supply. Years of reliable operation constructed with hard powder coated steel framework and stainless steel reel shafts. Designed, fabricated and built in Australia mean your trailer will work hard for years without corrosion or damage from the elements.

GPI-160



GPI-200

SPECIFICATIONS

	GPI-160	GPI-200
Engine	Honda GX160 petrol engine	Honda GX200 petrol engine
Pump (4 Outlets)	Davey Single Stage Firefighter Pump	Davey Twin Stage Firefighter Pump
Suction line	15m x 40mm suction line fitted with non-return valve and filter at dam end	
Fuel tank capacity	23 L to run continuously for 20hrs	
Dimensions	L=1550mm W=1100mm H=1060mm	L=1800mm W=1160mm H=1300mm
Water Tank	20 L water tank used to prime suction hose	
Tow ball	50mm tow ball attachment	
Outlet size	5m x 35mm outlet hose with cam-lock fittings	
Materials	Stainless steel reel shaft	
Type	Thick-walled, power-coated steel tube	
Paint finish	Powder-coated finish with zinc undercoat	
Protective function	5m twin core electrical cable and plug to turn off the Honda Engine	
Tyers	16 x 6.50-8 ply wheels, jockey wheel and 50mm coupling	18 x 8.50-8 Pneumatic tyres, jockey wheel and 50mm coupling
Function	Automatic shut-off technology	
Trailer	Powder coated steel trailer	Heavy duty galvanised steel trailer
Included	2 Year Manufacturer's Warranty	

